GOLDEN DRAGON CAPITAL

PRECURSOR CATHODE ACTIVE MATERIAL (pCAM)

Market Research Report



Table of Contents

Execu	utive Summary	2
1.0	Introduction	8
2.0	Product Characteristics and Specifications	10
3.0	Principal Production Methods	
3.1	Raw Material Requirements	
3	3.2 Processing Parameters which affect pCAM Production	25
3	3.2.1 Ammonia Concentration	
3	3.2.2 pH Value	
3	3.2.3 Reaction Temperature	
3	3.3.4 Reaction Control of pCAM of Different Components	
3	3.3.5 Reaction Time and Reaction Atmosphere	
3	3.3.6 Other Variables Affecting the pCAM Reaction Process	
3.4	pCAM Production Equipment	
3	3.4.1 Reactor	
3	3.4.2 Filtration and Washing Equipment	
3	3.4.3 Drying Equipment	52
3.5	Future Production Process R&D Trends	55
4.0	Cash Cost Analysis	61
5.0	Commercialisation	68
5.1	Rise of pCAM Production	68
5.2	Market Size Potential	
6.0	Competitive Landscape	74
6.1	CNGR Advanced Material Co., Ltd	78
6.2	GEM Co., Ltd	94
6.3	Zhejiang Huayou Cobalt Co., Ltd	
6.4	Guangdong Brunp Recycling Technology Co., Ltd	117
6.4	Lanzhou Jintong Energy Storage Power New Materials Co., Ltd	119
6.6	Overseas pCAM Companies	121
Refer	ences	129
Appe	ndix: 50,000tpa Ternary pCAM — Case Example	132
Discla	aimer	

Figures

Figure 1-Washing principle of a lithium ion batten.	0
Figure I: working principle of a lithium-ion battery	8
Figure 2: Lithium-ion battery packing types	8
Figure 3: pCAM is located within the lithium-ion battery midstream industry chain	9
Figure 4: pCAM is a black powder (illustrative)	9
Figure 5: pCAM SEM image (illustrative)	9
Figure 6: pCAM co-precipitation principal processing flowsheet	14
Figure 7: Continuous method principal processing flowsheet to produce pCAM	18
Figure 8: Nickel sulfate hexahydrate (illustrative)	19
Figure 9: Cobalt sulfate heptahydrate (illustrative)	.20
Figure 10: Manganese sulfate monohydrate (illustrative)	21
Figure 11: Sodium hydroxide (illustrative)	22
Figure 12: Liquid ammonia solution (illustrative)	22
Figure 13: Comparison of electrochemical performance of large and small particle cathode materials	.24
Figure 14: The specific surface area of the pCAM directly affects the crystal form, capacity and re	ate
performance of the cathode material	25
Figure 15: Process parameters that affect the physical and chemical properties of the pCAM	. 26
Figure 16: High nickel pCAM with different ammonia concentrations (left: 2g/L and right: 7g/L)	. 27
Figure 17: Increasing ammonia concentration leads to a decrease in nickel content	.28
Figure 18: Effect of ammonia concentration on pCAM, cathode and lithium-ion battery performance	. 29
Figure 19: Ammonia concentration and pH value of pCAM of different components	.30
Figure 20: PCAM morphologies obtained by reaction at different pH	.30
Figure 21: SEM of primary particles with different morphologies agglomerated into secondary particles	31
Figure 22: Influence of pH value on the performance of pCAM, cathode and lithium-ion battery	32
Figure 23: At low temperature, the primary particles are small and dense, and at high temperature, the	the
primary particles are coarse (50 degrees on the left and 60 degrees on the right)	33
Figure 24: Temperature influence on pCAM, cathode and lithium-ion battery performance	35
Figure 25: High nickel pCAM require higher pH and ammonia concentrations	.36
Figure 26: Tap density gradually increases with the increase of reaction time	37
Figure 27: NCM pCAM without nitrogen protection presents agglomerates of different sizes	37
Figure 28: Increasing solid content makes pCAM morphology more regular and the surface of the second	arv
narticles more dense (left: 10% and right: 20%)	38
Figure 29: Effect of solid content on pCAM, cathode and lithium-ion battery performance	39
Figure 30: Delationship between stirring speed and tap density	40
Figure 31: The lower the stirring speed the larger the size of the pCAM secondary particles	.40
Figure 31: The lower the stirring speed, the larger the size of the pCAM secondary particles	
Figure 32: Effect of the liquid on the merphology of the high nickel pCAM the precipitation time is 36b. (I	. 4 2
eil content is 9 Energy right; eil content is 2 nnm)	/.z
Sincontent is 9.5ppm, right, on content is 2ppm)	.43
Figure 34. Temperature control process	.44
Figure 35. Split-range temperature control method	.45
Figure 36: PCAM production equipment investment structure	.45
Figure 37: Schematic diagram of pCAM production line (intermittent method as an example)	.47
Figure 38: Schematic diagram of the pCAM reactors I and 2	.48
Figure 39: Filter press	.49
Figure 40: Working principal diagram of centrifuge	.49
Figure 41: Microporous filter	.50
Figure 42: Filter-wash two-in-one equipment	.50
Figure 43: Hot air circulation oven	52
Figure 44: Working principal diagram of hot air circulation oven	52
Figure 45: Disc dryer (left) and working principal of disc dryer (right)	53
Figure 46: Working principal diagram of rotary drum dryer	53
Figure 47: Flash dryer	.54
Figure 48: Working principal diagram of flash dryer	.54
Figure 49: Ordinary polycrystalline/secondary spherical cathode material	. 56

GOLDEN DRAGON CAPITAL

Figure 50: Single crystal cathode material	57
Figure 51: Schematic diagram of lithium-ion battery self-discharge caused by magnetic foreign matter	58
Figure 52: Schematic diagram of core-shell pCAM and ternary cathode structure	
Figure 53: Schematic diagram of gradient structure pCAM	
Figure 54: Schematic diagram of radial ternary pCAM structure	60
Figure 55: Ternary power battery cost structure (taking the NCM523 battery cell as an example)	61
Figure 56: Ternary cathode material cost structure (taking the NCM523 battery cell as an example)	62
Figure 57: nCAM raw materials account for a high proportion	67
Figure 58: Breakdown of operating costs of major Chinese nCAM (2021)	63
Figure 59: Nickel and cobalt sulfate prices (unit: x10,000 CNV per toppe)	65
Figure 59: Nickel and Cobait surface prices (unit: Xi0,000 CNY per tonne).	05
Figure 60. Terriary peak prices follow meter/cobait price changes (unit. 10,000 CNY per torme)	05 67
Figure 61: NCM911 vs NCM527 and NCM911 vs NCM622 price differences (Oct 2019 to Oct 2022)	
Figure 62. NCMBITVS NCM525 and NCMBITVS NCM622 price differences (Oct-2018 to Oct-2022)	
Figure 63: Global new energy vehicle sales forecast (2019 to 2026E)	68
Figure 64: Global Installed capacity of lithium power batteries forecast (2019 to 2026E)	69
Figure 65: China ternary battery installed capacity share (2021 to 2024E)	69
Figure 66: Global pCAM production (2019 to 2023)	70
Figure 67: China ternary cathode material production (2019 to 2023)	70
Figure 68: China single crystal ternary cathode material production (2019 to 2023)	71
Figure 69: The energy density of high-nickel batteries has increased significantly	72
Figure 70: High-nickel content of ternary pCAM continues to advance	72
Figure 71: Prices of ternary battery cells and LFP battery cells (CNY/Wh)	73
Figure 72: Global pCAM shipments forecast (2021 to 2026E)	74
Figure 73: China pCAM competitive landscape (2023)	75
Figure 74: Production capacity of leading pCAM companies (2019 to 2023E)	75
Figure 75: Gross profit margins of leading pCAM companies (2019 to 2022)	76
Figure 76: CNGR three production bases in Guizhou, Hunan and Guangxi	79
Figure 77: CNGR — Annual shipments of ternary pCAM (2020 to 2023-H1)	81
Figure 78: CNGR — Effective pCAM and cobalt tetraoxide production capacity and forecast	81
Figure 79: CNGR — unit tonne selling price is at the forefront among peers	82
Figure 80: pCAM processing fee per tonne (unit: x10,000 CNY)	82
Figure 81: The ratio of nickel and pCAM sales prices is currently over 65%	83
Figure 82: pCAM industry gross profit margin, the company is at a disadvantage among peers	84
Figure 83: CNGR — Sales share of the top five customers in 2022	88
Figure 84: CNGR sales to LGES (2018 to 2021)	89
Figure 85: CNGR — Main customers	89
Figure 86: CNGR — R&D expenses (2017 to 2022-H1)	90
Figure 87: pCAM industry expense ratios	91
Figure 88: CNGR — Operating income (2019 to 2024-Q1)	91
Figure 89: CNGR — New profit attributable to parent company (2019 to 2024-01)	92
Figure 90: CNGR — Gross profit margin and net profit margin (2019 to 2024-01)	92
Figure 91: CNGR — Expense ratios (2019 to 2024-01)	93
Figure 92: GEM — Business units	.94
Figure 93: GEM core-shell pCAM morphology	94
Figure 94: GEM — Ultra-bigh nickel products	95
Figure 95: CEM — Quaternary products	95
Figure 96: CEM — Core-shell-concentration gradient ternary materials	96
Figure 97: Schematic diagram of core-shell structure and full gradient structure	0C
Figure 98: CEM Co. 1 td — nCAM production bases in China	0C
Figure 99: CEM terpary pCAM production 2303 ± 2023 -H1	0C
Figure 30. CEM because production (2013 to 2023-11)	00
Figure 100. CEM PLAM production shipment structure (2019 to 2023-FI)	00
Figure 101. $OLM = P(AM)$ production consists forecast (2022 to 2026)	99
Figure 102. CEM's alobal new operative material supply chain (illustrative)	100
Figure 105. OEM S global new energy material supply chain (Illustrative)	. 101

GOLDEN DRAGON CAPITAL

Figure 104: Proportion of GEM top five customers (unit: million CNY, %)	102
Figure 105: GEM — New energy battery materials revenue structure (2019 to 2023-H1)	105
Figure 106: GEM — Gross profit margin of each new energy battery materials business	105
Figure 107: Huayou Cobalt — Overview of the ten-year layout of the ternary pCAM industry	
Figure 108: Huayou Cobalt — pCAM products	
Figure 109: Huayou Cobalt — Ternary pCAM production capacity forecast (2022E to 2025E)	
Figure 110: Huayou Cobalt — Business pillar coverage	110
Figure 111: Sales volume of major Chinese pCAM manufacturers (2018 to 2021)	111
Figure 112: Price gap between CNGR and Huayou is tightening year by year)	111
Figure 113: Comparison of ternary pCAM gross profit margins of different companies (2018 to 202	23)112
Figure 114: Huayou Cobalt — pCAM gross profit per tonne (10,000 CNY)	112
Figure 115: Huayou Cobalt — Ternary pCAM cost breakdown	113
Figure 116: Huayou Cobalt — Long-term ternary pCAM purchase orders (2022 to 2025E)	115
Figure 117: Brunp Recycling — Business layout	117
Figure 118: Jiang Yu, director of Jinchang Factory of Lanzhou Jintong Energy Storage Power Ne	w Materials
Co., Ltd. of Jinchuan Group, introduces the ternary pCAM products. Photo by Li Deyu	120
Figure 119: Ternary pCAM is a black solid powder. Photo by Li Deyu	120
Figure 120: Staff of Lanzhou Jintong Energy Storage Power New Materials Co., Ltd. of Jinchuar	n Group are
packing ternary pCAM products. Photo by Li Deyu	120
Figure 121: BASF proposed pCAM, CAM, and recycling facility in Bécancour, Quebec, Canada	121
Figure 122: Umicore — Kokkola plant in Finland	122
Figure 123: Umicore — Land plot reserved for pCAM production in Ontario, Canada	122
Figure 124: POSCO — Ternary pCAM (SEM Image)	124
Figure 125: POSCO — Ternary pCAM production line	124
Figure 126: pCAM plant (left) and cathode material production plant (right)	126
Figure 127: Tanaka Chemical Corp — Ternary pCAM	127
Figure 128: Tanaka Chemical Corp — Nickel-based materials	128

Tables

Table 1: GEM Co., Ltd — pCAM NCM 3 Series product specifications	10
Table 2: GEM Co., Ltd — pCAM NCM 5 Series product specifications	10
Table 3: GEM Co., Ltd — pCAM NCM 6 Series product specifications	11
Table 4: GEM Co., Ltd — pCAM NCM 7 Series product specifications	11
Table 5: GEM Co., Ltd — pCAM NCM 8 Series product specifications	12
Table 6: GEM Co., Ltd — pCAM NCA Series product specifications	12
Table 7: Comparison of mainstream ternary pCAM production methods	13
Table 8: Example of testing indicators for pCAM products	19
Table 9: Nickel sulfate for battery materials — China National Product Standard (HG/T 5919-2021)	20
Table 10: Cobalt sulfate for battery materials — China National Product Standard (HG/T 5918-2021)	20
Table 11: Manganese sulfate for battery materials — China National Product Standard (HG/T 4823-2023).	21
Table 12: Sodium hydroxide for industrial use — China National Product Standard (GB/T 209-2018)	22
Table 13: Ammonia solution— China National Product Standard (GB/T 631-2007)	23
Table 14: pCAM particle size determines the particle size of cathode materials	24
Table 15: Factors affecting pCAM end-product performance	26
Table 16: The main key pieces of equipment to produce ternary pCAM	46
Table 17: Common reactor product performance indicators	48
Table 18: Reactor volume and production capacity of a manufacturer	48
Table 19: Comparison of the mainstream filtering and washing equipment used in pCAM production	51
Table 20: Comparison of the mainstream drying equipment used in pCAM production	55
Table 21: Progress in the development of new technologies by leading pCAM manufacturers	61
Table 22: Upstream nickel resource layout of pCAM manufacturers (nickel content: tonnes)	64
Table 23: Comparison between pyrometallurgy and hydrometallurgy smelting processes	64
Table 24: Impact of material price changes on the total cost of pCAM (90% of material cost)	66
Table 25: Estimated cost per kWh of ternary cathode material products	66
Table 26: NCM811 has certain material cost advantages (average price in October 2022)	68
Table 27: Ternary cathode material product performance with different nickel content	71
Table 28: Main characteristics of ternary single crystal and polycrystalline materials	71
Table 29: List of ternary pCAM companies and their customers	76
Table 30: Comparison of ternary cathode materials with different crystal forms	77
Table 31: CNGR — pCAM product portfolio	78
Table 32: CNGR — pCAM production bases	80
Table 33: CNGR — Nickel front-end smelting layout	85
Table 34: CNGR — Nickel production forecast	85
Table 35: CNGR — Nickel back-end smelting lavout	86
Table 36: CNGR — Nickel self-supply ratio first increased and then decreased	86
Table 37: pCAM sensitivity analysis (self-supply rate and nickel sulfate market price to NCM81) pCAM	per
tonne gross profit)	87
Table 38: CNGR — pCAM sensitivity analysis (70% NCM811 and 30% NCM622)	87
Table 39: CNGR — Signed strategic supply agreements	
Table 40: CNGR — Core R&D technologies and application products of ternary pCAM	90
Table 41: Comparison of key indicators of China ternary pCAM companies	97
Table 42 [°] Strategic framework agreements between GEM and cathode material companies	101
Table 43: GEM — R&D projects related to pCAM and cathode materials	.104
Table 44: Huavou Cobalt — Ternary pCAM products and processes	.107
Table 45: Huavou Cobalt — Ternary pCAM production bases	109
Table 46: Huayou Cobalt — Ternary pCAM customers and supply agreements	
Table 47: Brunp Recycling — pCAM products	